Outdoor Enclosure

Pre-Quote Information Form



Requester's Contact Information:				
Name		Company		
Email/		Address/		
Phone		Zip Code		
1	Sizing the Cabinet		2	Chambers and Doors
	1. Number of equipment bays			1. Side chamber required
	2. RUs needed for customer equipment			2. Rear access: door, removable panel, none
	3. 19" or 23" rails			3. Security/Locking: Hex/pin or 216
	4. Number of equipment racks			4. Battery base required
	5. Equipment depth			
3	Climate Control		4	Mounting Options
	Choose one			Choose one
	1. Heat dissipation requirements			1. Pole mount
	2. Operating temperature range			2. Pad mount
	3. Ambient temperature range			3. Wall mount
	4. Active cooling (HX, HVAC, fans, etc.)			4. Other
	5. Passive cooling (sealed, vented)?			
5	AC Requirements		6	DC Power
	1. AC load center? (8 or 12 pos)			1. Capacity: Min Max
	2. Generator inlet (30A or 60A)			2. No-LVD, BLVD or LLVD
	3. 4x4 junction box			3. AC Input: 120vac or 208/240vac

4. 220vac 15A twist-lock receptacles

5. 220VAC 30A twist-lock receptacles

Please **SAVE** this form to your desktop. Then press the submit button below

4. Distribution: CBs _____ GMT _____

6. Battery disconnect

5. Reserve time:

Vertiv.com | Vertiv Headquarters, 1050 Dearborn Drive, Columbus, OH, 43085, USA

© 2020 Vertiv Group Corp. All rights reserved. Vertiv[™] and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.