

# CHLORIDE® CP70Z

AC Uninterruptible Power Supply System  
5 to 250 kVA (1-ph output) / up to 500 kVA (3-ph output)



## CHLORIDE® CP RANGE

Customized to user specification  
Full portfolio of industrial options

## BENEFITS

**Tailor made systems** to comply with most customer's specifications

**Ruggedized solutions** for demanding environments: high temperatures, vibrations, dust, elevation and moisture

**Efficient maintenance:**

- Easy front-access to all critical modules
- Enhanced safety thanks to the bypass line segregation in separate enclosure

**Smart access** to UPS data:

- User interface with large, colour touchscreen
- Embedded event logger (up to 2000 events) and capability to export recorded events via memory stick

## FEATURES

**Reliability:** Unique design which allows the UPS to continuously operate for at least 20 years at full load at 40 °C

**On-line double conversion:** UPS classified VFI SS 111 as per IEC62040-3

**Robust mechanical design:** the system withstands vertical and horizontal acceleration stress tests 0.5g as standard

**Galvanic isolation:** input and output transformers are included as standard

**Remote monitoring solutions:** Modbus, Profibus, Ethernet, IEC61850, volt-free contact, monitoring software

**Full compatibility** with lead acid and nickel cadmium batteries, sealed or vented

Chloride® CP70Z industrial Uninterruptible Power Supply system (UPS) is the flagship product of the Chloride® range. It combines conservative design (SCR/IGBT) with proven digital control to ensure the utmost reliability in any electrical and environmental conditions.



## Range Overview

Associated with an industrial stand-by battery, Chloride® CP70Z protects critical industrial AC equipment and processes from the damaging effects of power interruptions and variations.

The UPS uses the patented digital vector control technology which increases the performances of power components, enables an active conditioning of the load and allows personalized system settings. The result is improved reliability for the process and enhanced safety for the personnel.

Chloride® CP70Z systems form a range of single-phase or three-phase output AC UPS systems with a range of ratings from 2.5 kVA to 120 kVA as standard. This range offers a wide choice of DC battery voltages and of output voltages.

A Chloride® CP70Z system can also be customized to meet higher power needs, up to 250 kVA single-phase output or up to 500 kVA three-phase output.

To further improve load availability and process reliability, Chloride® CP70Z is able to operate in dual parallel configuration, with single or dual batteries, with centralized or distributed reserve line, and can include a DC and/or AC bus-tie.

## Applications

- Oil and Gas industries, offshore and onshore
- Refining and petrochemical plants
- Power generation plants
- Rail transport



Example of Chloride® CP70Z-40kVA-12P-220Vdc-230Vac-1ph

## Technical Data

### RATINGS

#### OUTPUT POWER<sup>(1)</sup> (kVA) vs DC INTERMEDIATE VOLTAGE (Vdc)

Output Power (kVA)	5	10	20	30	40	50	60 <sup>(2)</sup>	80	100	120 <sup>(2)</sup>
110-120 Vdc	5	10	20	30	40	50	60 <sup>(2)</sup>	-	-	-
220-240 Vdc	-	10 <sup>(2)</sup>	20	30	40	50	60	80	100	120 <sup>(2)</sup>
400 Vdc <sup>(3)</sup>	-	-	-	-	40	50	60	80	100	120

### INPUT

AC voltage	3 x 400 V (380, 415) <sup>(4)</sup>
Voltage tolerance	+/- 10 %
Frequency	50 Hz (60 Hz)
Frequency tolerance	+/- 5 %
Inrush current	≤ 15 x In <sup>(4)</sup>

### INTERMEDIATE DC CIRCUIT

Nominal DC voltage	110-120 / 220-240 / 400 V
Voltage stability (with input within tolerance)	+/- 1 % in float mode +/- 1.5 % for parallel rectifiers
Voltage ripple	≤ 1 % RMS, in float mode, battery disconnected
Rectifier current limitation	I nominal

### OUTPUT

Available ratings	See table (at PF 0.8 lagging)
AC Voltage	
• Single phase	1 x 230 V (220, 240) ; 1 x 110 V (115, 120) <sup>(4)</sup>
• Three phase	3 x 400 V (380, 415) ; 3 x 220 V (200, 208, 230) <sup>(4)</sup>
Frequency	50 Hz (60 Hz)
Frequency stability	
• With internal oscillator	+/- 0.05 %
• With reserve synchronism	+/- 3 % (from 1 to 5 % adjustable)
Voltage stability (for 0 to 100 % load variation)	
• Static	+/-1 % (+/-2 % for parallel systems)
• Dynamic	VFI SS 111 as per IEC/EN 62040-3, class 1
Inverter overload capability	
• 1 minute	150 % of nominal power
• 10 minutes	125 % of nominal power
Short circuit clearance (in % of nominal current)	
• 1-ph output	250 % / 100ms - 175 % / 5s
• 3-ph output	Ph-Ph: 315 % / 100 ms - 220 % / 5 s Ph-N: 190 % / 100 ms - 135 % / 5 s
Harmonic voltage distortion	
• With 100 % linear load	< 3 %
• With 100 % non-linear load	SS as per IEC/EN 62040-3
Allowable power factor	0.5 lagging to 0.5 leading <sup>(5)</sup>
Allowable crest factor	up to 3/1

### BATTERY

Type	Lead acid or nickel cadmium, vented or recombination
Autonomy	From few minutes to several hours, on request
Battery current limitation (typical, float & boost modes)	0.1 C (lead-acid battery) 0.2 C (nickel-cadmium battery)

### GENERAL DATA

Operating temperature	0 to 40 °C <sup>(4)</sup>
Storage temperature	-20 to +70 °C
Relative humidity	< 95 % non condensing
Operating altitude	1000 m max without derating <sup>(4)</sup>
Cooling	Forced ventilation
Efficiency	Up to 90 % according to rating
External protection	IP 20 <sup>(4)</sup> according to IEC 60529
Noise (at 1m in front of the unit)	60 – 75 dB according to rating
Cabinet colour	Grey RAL 7032 <sup>(4)</sup>
Dimensions	Varying according to ratings and options

### CONFORMITY

Low voltage directive	2006/95/EC and 2014/35/EU
EMC directive	2004/108/EC and 2014/30/EU

CE Mark

(1) at power factor 0.8 lagging

(2) 1-ph output only

(3) Up to 250 kVA 1-ph output or up to 500kVA 3-ph output on request

(4) other available on request

(5) derating may apply

### OPTIONS

Consult us for any other requirements, subject to feasibility

Rectifier-charger	<ul style="list-style-type: none"> <li>• 12-pulse rectifier</li> <li>• Harmonic filter on 12P for THDi = 5 % (+/- 1pt)</li> <li>• Voltage ripple filter</li> <li>• Blocking diode</li> <li>• Other input voltage (3 x 190 to 3 x 690 VAC)</li> <li>• Inrush current limitation to 5 x In</li> <li>• Surge and Lightning protections</li> </ul>
Battery line	<ul style="list-style-type: none"> <li>• Battery circuit protection box</li> <li>• Battery reversed polarity detection</li> <li>• Battery low-voltage disconnection contactor (LVD)</li> <li>• DC earth fault detection</li> <li>• Battery black start</li> <li>• Battery room temperature sensor</li> <li>• Battery monitoring system (Chloride® BMS)</li> <li>• Battery cabinet / rack</li> </ul>
Inverter	<ul style="list-style-type: none"> <li>• Other output voltage (1 x 110 to 3 x 690 VAC)</li> <li>• Inverter oversizing</li> </ul>
Bypass line	<ul style="list-style-type: none"> <li>• Bypass isolator(s)</li> <li>• Bypass transformer (H class)</li> <li>• Bypass stabilizer (servo-controlled)</li> <li>• Backfeed protection</li> </ul>
System	<ul style="list-style-type: none"> <li>• Parallel configurations</li> <li>• Input / intermediate / output isolators</li> <li>• AC distribution</li> <li>• Earth fault detection or monitoring</li> <li>• Internal cabinet lighting</li> <li>• Anti-condensation heater</li> <li>• UPS cabinet temperature monitor</li> </ul>
Mechanical	<ul style="list-style-type: none"> <li>• External ingress protection up to IP42</li> <li>• Top cable entry</li> <li>• Specified color of panels</li> <li>• Special feet height (200mm or 300mm)</li> <li>• Special keylock</li> <li>• Non-magnetic gland plate (brass or aluminum)</li> <li>• 2 mm side panels thickness</li> <li>• Specified cabinet identification (tag, nameplate)</li> <li>• Anti-seismic design</li> </ul>
Communication	<ul style="list-style-type: none"> <li>• Front panel analogue meters (72x72, class 1.5 or class 1)</li> <li>• Transducers 4-20mA</li> <li>• Additional volt-free contacts</li> <li>• Modbus RTU (RS232 or RS485)</li> <li>• Modbus / TCP</li> <li>• Profibus</li> <li>• IEC61850 protocol</li> <li>• PPVIs monitoring software</li> <li>• Mimic panel:                             <ul style="list-style-type: none"> <li>• Passive mimic of the system</li> <li>• Active mimic with integrated LEDs</li> </ul> </li> <li>• Lamp indicator on front panel (22 mm diameter)</li> </ul>

### STANDARDS

IEC62040-1:2008 +AMD1:2013	Uninterruptible power systems (UPS) - Part 1-2: General and safety requirements for UPS in restricted access locations
IEC62040-2:2006	Uninterruptible power systems (UPS) - Part 2: Electromagnetic compatibility (EMC) requirements
IEC62040-3:2011	Uninterruptible power systems (UPS) - Part 3: Method of specifying the performance and test requirements
IEC61439-1:2011	Low voltage switchgear and controlgear assemblies - Part 1: General rules
IEC60529:1989 +AMD1:1999	Degrees of protection provided by enclosures (IP Code)
IEC60076-11:2004	Power transformers - Part 11: Dry type transformers

VertivCo.com/chloride | Global & Europe, Vertiv Industrial Systems SAS,  
30, Avenue Montgolfier  
BP 90 - 69684 Chassieu - France  
T: +33 (0)4 78 40 13 56  
Industrial.Power@VertivCo.com

To find contact in your region, please visit [www.VertivCo.com](http://www.VertivCo.com)